



# Power Switches

Each switch comes standard with 6-foot input and output cords. Standard input is female DC barrel plug; output is 90° male barrel plug.

## OVERVIEW

Two-position rocker switch mounted in metal housing.

Switch housings have glossy black powder coat finish.

Cord color is black with PVC insulation over plated copper conductor.

Double-molded process for barrel plugs provides longevity.

UL-certified AWM style 1185 wire.

Heavy 16-gauge wire reduces voltage loss.

Current rating of 8 amps.

Working temperatures up to 125° F.

Assembly utilized as part of a class 2 circuit, UL recognized.

## SWITCH OPTIONS



### Single Switch

(Allows for control of single transformer with single switch.)



### Dual Switch

(Use for CL and CR switching, power with one or two transformers.)



### Two-Pole Switch

(Allows control of two transformers with a single switch.)

## MOUNTING STYLES

(Each provided with two mounting holes.)



### Over

(Press on top of 1" tube, secure with screws.)



### Under

(Slide under 1" tube, secure with screws.)



### Flush

(Mount below counter top, fasten with screws.)



Connects seamlessly with existing Lighting for Impact power systems for easy installation!

# Motion Detection



## OVERVIEW

Infrared PIR motion sensor.	6-foot range, 120° viewing angle.	Sensor triggers power immediately on sensing movement.	Power remains on until sensor timer duration has elapsed.	Standard sensors are available with 75- and 150-second timers.	All provided with multiple mounting options including screws, zip ties, and 3M tape.
-----------------------------	-----------------------------------	--	---	--	--

## SENSOR RANGE

