




C-Channel



DESCRIPTION:

C-channels are used for under-shelf lighting, as they protect the LED strip and attach easily to a variety of shelving applications. Mounting options include: adhesive, clip and magnet.

- Low profile
- Custom lengths for every application
- Versatile mounting options for all surfaces
- Four LED color temperature options
- Optional light diffuser
- Built-in strain relief protects cord from retail environment
- UL Listed
- 5 Year Warranty

SPECIFICATIONS:

LED Type	Standard	Bright
Recommended Target Distance	< 12"	12–24"
Intensity	150 lm/Foot	350 lm/Foot
LED Chip	Epistar SMD 2835	
Power/Chip	0.2 Watts	0.5 Watts
CRI	Ra > 80	
Lumen/Chip	24–26	60–65
Diodes/Foot	18	
Efficiency	105–110 lm/W	115–120 lm/W
Power	1.37W/Foot	2.93W/Foot
Connector	2.1mm x 5.5mm DC barrel Connector on 22-gauge wire	
Listing	UL E474996	
CCT	3,000/4,000/5,000/6,000K	
Beam Angle	120 degrees	
Lifetime	> 50,000 Hours	
Voltage	12V	
PCB Dimensions	0.32" x 1.97"	
Dimmable	Yes	