



23.9mm 0.94"

Wall Washer — Standard





DESCRIPTION:

Wall Washer — *Standard* units, are used to light merchandising on varied wall treatments like slatwall, pegged merchandising — and also work very well in enclosed areas, such as cabinets and locked cases. Two 180° pivoting brackets are provided for mounting.

- Silver housing is anodized aluminum
- Aluminum body with 4 mm tempered glass optical lenses
- Versatile mounting options for a variety of surfaces
- Built-in strain relief protects cord from retail
 environment
- Operates on 12V low voltage, safe and efficient
- Works seamlessly with Lighting for Impact power systems, which are UL listed
- 5 Year Warranty

SPECIFICATIONS:

LED Type	Standard		
Recommended Target Distance	Up to ~4' (48")		
LED Chip	SMD 5050		
CRI	Ra > 80		
Lumen	30"/595, 46"/935		
Diodes/Foot	15		
Efficiency	80-85lm/W		
Connector	5.5 x 2.1mm barrel plug on 24AWG wire		
ССТ	Pure 5000K		
IP Rating	IP20		
Beam Angle	30°		
Lifetime	> 50,000 Hours		
Voltage	12V		
Dimensions	1" W x 2.3" H		
Dimmable	Yes		

Part Number	Nominal Length	Actual Length	Wattage	Lumen Output
WW-46-6A-6C-PV	46"	1,179 mm	11	935
WW-30-6A-6C-PV	30"	748 mm	7	595